

EVOLite® LINESMAN MICRO PEAK - WHEEL RATCHET

EVOLite® LINESMAN COMBINES ALL THE FEATURES OF THE EVOLite®, WITH A 4-POINT CHINSTRAP HARNESS AVAILABLE IN VENTED OR NON-VENTED OPTIONS

TECHNICAL SPECIFICATION

HEAD PROTECTION

INSTRUCTIONS FOR USE

- Fit helmet on head and fasten strap to ensure fit
- For adequate protection this helmet must be worn with peak facing forward
- Ensure the helmet is adjusted to the size of the user's head



SHELL:

High strength engineering grade ABS which has been UV Stabilised




WEBBING HARNESS:

HDPE Strap & Webbing Clips with Polyester Webbing Straps



CHAMLON™ SWEATBAND:

Egyptian cotton core with porous PU coating for maximum sweat absorption. PH neutral, dermatologically tested



WHEEL RATCHET:

The Revolution® Wheel Ratchet is the new easy to use wheel ratchet adjustment system to create a firm comfort fit with added security



CONFORMITY

- Conforms to EN397 & EN50365
- EN 50365 for Helmets for use in low voltage installations
- EC Certificate Number 00279, issued by BSi Product Certification
- Meets the retro reflective performance requirements of EN12899 when fitted with CR2 Reflective Kit
- Meets optional Molten Metal Splash performance
- Non-vented version meets optional Electrical Insulation requirements
- Wide size range. Slip or wheel ratchet - High comfort fit
- Available vented or non-vented. Available with mid or micro peak
- Company personalisation available by printing

CLEANING & MAINTENANCE

- The unit may be cleaned with soap and warm water and dried with a soft cloth
- The helmet should not be cleaned with chemical or abrasive cleaners
- The helmet should be stored out of direct sunlight
- The helmet should be stored away from chemicals and extremes of temperature



MANUFACTURING FOR SAFETY
WWW.JSP.CO.UK

UKSALES@JSP.CO.UK
TEL: +44 (0)1993 826050



EVOLite® LINESMAN MICRO PEAK - WHEEL RATCHET

PRODUCT CODE: AJC240-00 - 00

EVOLite® LINESMAN COMBINES ALL THE FEATURES OF THE EVOLite®, WITH A 4-POINT CHINSTRAP HARNESS

TECHNICAL SPECIFICATION

HEAD PROTECTION

DIMENSIONS OF OUTER PACKAGING

Quantity: 10

Weight: 3.2kg (Approx.)



HEIGHT:
450mm

LENGTH:
580mm

WIDTH:
240mm

HELMET FEATURES

EN STANDARD	EN397 EN50365	Yes Yes
PERFORMANCE	Impact Resistance Lateral Deformation Electrical Insulation (Non-vented shells only)	Yes 50 Joules Yes Yes: EN397 440v EN50365 1000v
TEMPERATURE RESISTANCE	Molten Metal (MM) +50°C -30°C	Yes Yes Yes
SHELL MATERIAL	ABS Recyclable UV Stabilised	Yes Yes Yes
HARNESS MATERIAL	HDPE Textile	Yes Yes
OPTIONS	Universal Accesories Reflective CR2 option Integrated Eyewear Micro Peak	Yes Yes Yes Yes
HARNESS SYSTEM OPTIONS	JSP 3D Wheel Ratchet 6 pts	Yes Yes Yes
CHINSTRAP OPTIONS	4 pts 2 pts	Yes Yes
LOGO OPTIONS	Front Rear Side MOQ Logo Individual Name	Yes Yes Yes 10 Yes

DIMENSIONS OF HELMET

Size: 530 - 640mm

Weight: 299g (Approx.)



HELMET COLOURS

Insert the following two digit number in place of the dashes in the product code of your desired helmet



LIMITATIONS OF USE

Protection will only be offered if the helmet is fitted correctly

Any helmet subjected to severe impact should be replaced immediately. Do not apply paint, solvents or adhesive labels except in accordance with instructions from the manufacturer

The harness, when in contact with the skin may cause allergic reactions to susceptible individuals. If this occurs leave the hazard area, remove the helmet and seek medical advice

The attention of users is also drawn to the dangers of modifying or removing any of the original component parts, other than as recommended by the manufacturer



MANUFACTURING FOR SAFETY
WWW.JSP.CO.UK

UKSALES@JSP.CO.UK
TEL: +44 (0)1993 826050

